
LED EDGEGLOW LIGHTBOX



FEATURES

- Sleek panel profile (less than 1/2")
- Available as single or double-faced
- Custom sizes and colors available
- Various mounting options
- Easy to install & replace graphics


- Available in 3500K, 4100K, 5600K, & 6400K
- Up to 60,000 hrs useable life of high intensity LEDs
- Panel sizes up to 8' x 4'
- Connecting cables available for daisy chain
- UL approved

\circ	FC	\sim $^{\prime}$	ΥТΙ	\sim $^{\prime}$	JC.
oг	EC	\cup_F	٩П	Uľ	VO

LED Chip Size		3020			
LEDs / Ft	18	42	54	27	
LED Wattage/Ft (2 Edge@12V)	2.8	6.7	8.6	13.0	
Lux Range	2500 to 6000 Lux				
Max LED Edge Length (Inches)		96"			
Max Inches Between Edges		48"			
LED Operating Temp	-30°C to 85°C				
LED PCB & Circuit	FR4, Copper Circuit				

LED Color Temp	3000K, 3500K, 4100K, 5600K, & 6400K		
Lamp Life (L70@45°C)	60,000 hrs		
Panel Material	Clear Acrylic		
Wiring Specs	22ga (AWM 2468x2C, AWM 2464x2C)		
Connector Specs	2.1mm DC Barrels		
Environment	Indoor		
Certifications	UL		
Warranty	3 Year		


LED EDGEGLOW LIGHTBOX ORDERING INFORMATION





LED EDGEGLOW LIGHTBOX







A 2

A=Chrome 1=1 B=Chrom Swivel Male 2=2 Swivel

Top Mount Qty

Туре

Example: EGK-A2B2-A0960X2-00

В

Bottom

Mount

Туре


2


Qty

Α

Cable

Туре









EG

Model

EG=

Edge Glow LED

K

Kit Type

K=Mount